

Mini Transmitter MRC-10



MRC-10 is a small and portable wireless set with VHF mic, frequency selection of IR, with 100 frequencies, easy to set and operate, working distance about 30 meters.

Features

VHF transmitter;

3 way to carry and use: collar clips, hanging, hand held or set on table stand;

Small and compact size

Specification

Model No.	MRC-10
VHF range	220~270MHz
Deviation	30Hz, and limiter
S/N Ration	>60 dB
THD	< 1%
Function	Mute Control (Noise Lock)
Frequency Response	50Hz~18KHz
Output Intensity	0~400mV

Mini Transmitter MRC-12A MRC-12B



MRC-12A & MRC-12B is a small and portable wireless set with VHF mic, ideal for KTV, school, hall, family and party.

Features

VHF transmitter 210~270MHz quartz control phase locked1;

High fidelity cartridge module;

Super low background noise;

High efficiency batteries consumption design.

Specification

Model No.	MRC-12A & MRC-12B
VHF range	210~270MHz
Deviation (Max)	25KHz
Frequency Response	50Hz~13KHz
S/N Ration	>95 dB
THD	< 0.2%
Microphone Power	9V
Cover Distance	50 meter
Wireless Receiver Power	DC1.5V

Active Speaker with Wireless Mic T-30



T-30 is a wall mounting active speaker with a wireless Bluetooth mic, 2 way 5.25" speaker drivers handle 30W power of sound. The speaker delivers high quality of human voice, noise sound can be filtered, and clean sound be picked up by microphone.

Features

5.25" speaker driver;

Rated power 30 Watts, max power 50 Watts;

Bluetooth communication

Specification

Model No.	T-30
Speaker	5.25" woofer + 1" tweeter
Power / Max	30W / 50W
Audio Input	RCA input
Output	1 RCA Audio Output
S/N Ratio	> 80dB
Volume Control	Main Volume & Tone control
Sensitivity	90 dB
Transmitter Use	Last 6-8 hours per time
Power Supply	220V 50/60Hz (Speaker) 3.7V Li Battery (Transmitter)
Wireless Microphone	Handheld or headset

Active Speaker with Wireless Mic T-243



T-243 is a wall mounting active speaker with a wireless 2.4G mic, 4" speaker drivers handle 30W power of sound. The speaker delivers high quality of human voice, noise sound can be filtered, and clean sound be picked up by microphone.

Features

4" speaker driver;

Rated power 30 Watts, max power 50 Watts;

GFSK Mode

Specification

Model No.	T-243
Speaker	4" speaker driver
Power / Max	30W / 50W
Audio Input	RCA input
Input	1 Mic inputs + 1 Audio input
S/N Ratio	> 80dB
Volume Control	Echo & Tone control
2.4G Mode	2402~2482MHz
Sensitivity	91 dB
Transistor Use	Last 6-8 hours per time
Power Supply	220V 50/60Hz (Speaker) 3.7V Li Battery (Transistor)
Wireless Microphone	Handheld or headset

COMMERCIAL AUDIO SYSTEM

Bluetooth Microphone Amplifier



T-206 / T-212

Meeting room / Classroom use

ARTONE

The classroom amplifier T-206 / T-212 comes with built-in audio sources USB, SD card, FM tuner and bluetooth player for audio play. A bluetooth microphone allows teacher or lecturer gives clear and bright speech to classroom and students, high quality of sound transmission and no interference from other classroom at all. Bring-and-speak, less than 5 seconds for wireless connection.



Features

- Stereo Amplifier RMS power dual 60W x 2 or 120W x 2 @ 8Ω;
- Built-in USB, SD card, FM tuner and Bluetooth as audio sources;
- Bluetooth microphone for clear wireless talking without interference;
- Wireless microphone coverage distance 20 meters;
- Minimum interference among each sound system;
- Collar clip and headset microphone for option, volume control on mic transmitter;
- 2 wired MIC inputs, 2 AUX inputs;
- Treble, bass, echo, mic, aux volume control;
- Shortcircuit, overload, high temperature, clip protection;
- Best for classroom, conference room, etc



Specification

Model No.	T-206	T-212
Rated Power	60W x 2	120W x 2
Speaker Output	8Ω	
Input Sensitivity (1m/1w)	Mic: 5mV/600Ω unbalanced 6.3mm phone jack input AUX:350mV/10KΩ RCA input	
Frequency Response	35-18KHz	
S/N Ratio	Mic: 66 dB AUX: 80 dB	
Material & Finish	Alu panel & lack color	
Dimension (mm)	430 x 300 x 78 mm	
Weight (kg)	8.8 kg	12.5 kg

